



*High-Clearance
Sprayers*



800-825-3346 • Sales@LeeAgra.com

LEE SPIDER *Classic*

In recent years growers have struggled with resistant weeds that can't be controlled by spraying over the top of the crop. Farmers want a small spot sprayer similar to the ones we built in the 1990s that can be configured as a spot sprayer, a boom sprayer, a wiper/boom or endless other combinations.

With 15in. tires and wheels, durable hydraulic circuit and a small engine, we are proud to present the Spider Classic.



LEE SPIDER

The Lee Spider Diesel Power solves the problems of spraying in difficult conditions with increased horsepower, crop clearance and an array of options.

★ **Diesel Power**
48HP turbo diesel for extra power in the field.

★ **Larger Tires**
Option: Larger 7.2 x 30in. wheels and tires give maximum crop clearance.
Standard: 7.5in x 20in.



LEE PREDATOR

Specialty Crop Sprayer

★ **Specialty Market**
The LEE Predator was produced for nurseries, plot/research spraying, and produce markets.

★ **Hoop House Sprayer**
Fly through greenhouses and go where no other sprayers dare. Tall enough to glide over crops but short enough to fit under the roof.

★ **Power and Agility**
The diesel engine is coupled with a lightweight footprint so you can get more done in less time.

★ **A/C Cab Upgrade**
Upgrade the open rider station to the new enclosed cab, which provides protection and comfort while giving you a full view of the crop.



AVENGER

by LEE

Our Largest Platform



- ★ **Trailblazer**
Power your way through challenging environments with the 70HP Yanmar Diesel engine.
- ★ **Charcoal Filtered Cab**
Increased air quality with the oversized operator's cabin.
- ★ **Small Footprint**
The high clearance and oscillating frame allow the tractor to glide over the crop.

- ★ **Hydraulic Adjustments**
Adjust your tractor to fit your crop! The Avenger utilizes hydraulic legs to automatically adjust its width and height for multiple crop configurations.
- ★ **Highly Configurable**
Choose from endless options to make the perfect tractor to fit your application.
- ★ **Tool Carrier**
Capable of carrying a wide assortment of equipment.



Shown with optional equipment.



SPECS		
Engine	20HP Honda or Kohler	48HP Diesel Engine
EPA Tier Rating	N/A	Tier 4 Final
Top Speed	8MPH	11MPH
Row Width	Manually adjustable 60in. - 90in.	Manually adjustable 60in. - 90in.
Underframe Clearance	Manually adjustable 36in. - 66in.	Manually adjustable 42in. - 72in.
Dry Weight	2700lb.	3300lb.
Turning Radius	Articulating frame with 90in. minimum turning radius.	Articulating frame with 90in. minimum turning radius.
Tire / Wheel	7.60in. x 15in. Cleated tire with modular wheel.	Standard: 7.5in. x 20in., Optional: 7.2in. x 30in.
Rider Station	Open with shade canopy, adjustable seat and seatbelt.	Open with shade canopy, adjustable seat and seatbelt.
Solution Tank	110 gallons.	Optional up to 150 gallons.
Solution Pump	Optional 12v 5.3 GPM / 60 PSI.	Optional Hydraulic Centrifugal/Piston Pump.
Brakes	Dynamic: Hydrostatic Static: Hydraulic circuit lock.	Dynamic: Hydrostatic Static: Spring-applied hydraulic released wet disc.
Steering	Side steering wheel.	Center steering wheel.
Speed Control	Manual/Foot Shift	Manual/Side Shift or optional Foot Shift
Running Lights	None.	Amber/red rear lights.
Work Lights	None.	Wide angle LED Work Lights with directional boom lighting.
Fuel Tank Capacity	12gal.	14gal.
Hydraulic Reservoir Capacity	13.5gal.	20gal.
Aux Hydraulic Flow	Optional	Optional
Wheel Base	85in.	85in.
Machine Width	90in.	90in.
Machine Height	94in. (lowest position)	100in. (lowest position)



SPECS		
Engine	70HP Diesel Engine	70HP Diesel Engine
EPA Tier Rating	Tier 4 Final	Tier 4 Final
Top Speed	12MPH	21MPH
Row Width	Hydraulically adjustable 72in. - 120in.	Hydraulically adjustable 72in. - 120in.
Underframe Clearance	Hydraulically adjustable height 54in. - 78in.	Hydraulically adjustable height 59in. - 84in.
Dry Weight	5100lb.	8700lb.
Turning Radius	Articulating frame with 96in. minimum turning radius.	Articulating frame with 150in. minimum turning radius.
Tire / Wheel	Standard: 7.2in. x 30in., Optional: 9.5in. x 32in.	9.5in. x 32in. Tire and Wheel.
Rider Station	Open air or optional enclosed cab with A/C and filtration.	Luxury cab with heating, cooling & air suspension seat.
Solution Tank	Optional up to 200 gallons.	Optional up to 300 gallons.
Solution Pump	Optional Hydraulic Centrifugal/Piston Pump.	Optional Hydraulic Centrifugal/Piston Pump.
Brakes	Dynamic: Hydrostatic or Static: Spring-applied.	Dynamic: Hydrostatic or Static: Spring-applied.
Steering	Center steering wheel.	Center steering wheel.
Speed Control	Manual hydrostatic. Optional cab with Canbus controls.	Electronic GPS
Running Lights	Amber/red rear lights.	Amber/red rear lights.
Work Lights	Wide Angle LED Work Lights with directional boom lighting.	Wide Angle LED Work Lights with directional boom lighting.
Fuel Tank Capacity	20gal.	21 gal.
Hydraulic Reservoir Capacity	22.5gal.	24gal.
Aux Hydraulic Flow	15GPM @3,000PSI	35GPM @3,000PSI
Wheel Base	96in.	115in.
Machine Width	101in.	101in.
Machine Height	113in. (lowest position)	137in. (lowest position)





LeeAgra, Inc. manufactures quality equipment designed to stand the test of time. Since 1949 our diverse product lines have served the agricultural, energy and construction industries. Our products are now sold and serviced worldwide.

Our priority is simple: We are dedicated to manufacturing and delivering innovative and high-quality products while giving full service and support to you, our customer.

Lynn Lee
President

**For videos, pictures, and more
please visit:
LeeAgra.com**

**(800) 825-3346
(806) 687-5790
Sales@LeeAgra.com
Parts@LeeAgra.com**

**LeeAgra, Inc.
117 E. 70th St.
Lubbock, TX 79404**

